

Design and Optimization of Next-Generation Perovskite Solar Cells for Sustainable Energy

JOHN DAVIS

Copple High School, TX, Copple

Published, Apr, 2025

Perovskite solar cells (PSCs) have rapidly emerged as a transformative technology in the field of photovoltaics, offering a compelling combination of highpower conversion efficiencies, low-cost fabrication, and tunable optoelectronic properties. This review provides a comprehensive overview of the latest advancements in the design and optimization of PSCs aimed at promoting sustainable energy solutions. Key focus areas include compositional engineering of perovskite materials, interface modification strategies, device architecture innovations, and stability enhancement techniques. The integration of perovskites into tandem solar cells and the development of scalable fabrication methods are also discussed in the context of commercial viability. By addressing current challenges such as material toxicity, environmental stability, and large-scale manufacturing, this review outlines the critical steps needed to transition PSCs from laboratory research to widespread deployment in the global energy market.

1. INTRODUCTION

The rapid emergence of perovskite solar cells (PSCs) has revolutionized the field of photovoltaics, presenting substantial advancements in power conversion efficiencies (PCEs) and cost-effectiveness. PSCs distinguish themselves through their adaptable properties, which allow for tunable absorption spectra and flexible application methods. This versatility underscores their significance in the quest for sustainable energy solutions, offering a promising alternative to traditional silicon-based solar technologies. Moreover, the potential of PSCs to significantly reduce the carbon footprint of solar energy production aligns them with global sustainability goals. By integrating these cutting-edge devices into the energy mix, PSCs hold the promise to facilitate a substantial shift toward more sustainable and environmentally friendly energy systems. This review provides a comprehensive summary of the design principles and optimization strategies being employed to advance next-generation PSCs. It begins with discussing materials engineering, including compositional tuning and lead-free alternatives. The following sections explore interface engineering for charge extraction for enhancing long-term stability.

A. Materials Design

In the pursuit of optimizing perovskite solar cells (PSCs) for enhanced efficiency and stability, significant attention has been directed toward the design of halide perovskite compositions. Among these, formulations such as $\text{FA}_{1-x}\text{MA}_x\text{Pb}(\text{I}_{1-x}\text{Br}_x)_3$ and the Cs/FA/MA triple-cation approach have demonstrated considerable promise. These compositions are crafted to fine-tune

the energy bandgap, enhancing the device's ability to absorb sunlight and convert it into electricity efficiently. Furthermore, transitioning to lead-free alternatives, including elements like Sn^{2+} and Bi^{3+} , addresses environmental and toxicity concerns while striving to maintain competitive performance levels [1]. Collectively, these innovations in material engineering are pivotal in advancing the overall stability and application potential of PSCs, which remains a crucial objective as the field continues to evolve.

B. Interface Engineering

To enhance the performance of perovskite solar cells (PSCs), the optimization of interface engineering plays a crucial role, focusing particularly on electron and hole transport layers (ETLs and HTLs, respectively). ETLs such as titanium dioxide (TiO_2), tin dioxide (SnO_2), and zinc oxide (ZnO) are pivotal for facilitating efficient electron extraction and transport, which significantly minimizes recombination losses and boosts the overall power conversion efficiency of PSCs. On the other hand, optimizing HTLs employing materials like Spiro-OMeTAD, nickel oxide (NiO_x), copper thiocyanate (CuSCN), and poly-triarylamine (PTAA) is essential for effective hole extraction and transport, further enhancing device stability and efficiency. As indicated by Azri et al., both ETLs and HTLs play key roles in overcoming defects associated with interface losses, thereby promoting better electronic properties [2]. Through advances in interface engineering, PSCs can achieve greater efficiencies and longer operational lifetimes, making them more viable for commercial

applications in sustainable energy solutions.

C. Device Architecture

Diverse device architectures are integral to enhancing the performance of perovskite solar cells (PSCs). Among these, mesoporous structures exemplify a classic approach where the perovskite layer is infiltrated into a scaffold, providing a large surface area for charge separation and collection [3]. Conversely, planar heterojunction structures, featuring a flat interface between layers, offer simpler fabrication processes and have been shown to achieve noteworthy efficiencies by minimizing layer defects. Moreover, inverted structures, which invert the sequence of electron and hole transport layers compared to traditional PSCs, allow for better stability and are compatible with flexible substrates. Structural optimization techniques, such as reducing defect densities and enhancing carrier mobility, underpin the potential of these diverse architectures to meet the demands of high-efficiency renewable energy solutions, contributing to the broader viability and commercial appeal of PSCs.

Furthermore, the stability of perovskite solar cells (PSCs) is critically enhanced through advanced encapsulation methods that employ materials like polymer resins and atomic layer deposition (ALD). These techniques effectively protect the perovskite layers from environmental degradation, thereby extending the operational lifetime of the devices [4]. Additionally, intrinsic stability can be achieved by engineering the perovskite material itself to reduce its susceptibility to moisture and thermal stress. For instance, modifying the crystallinity and composition of perovskite layers not only augments their structural robustness but also mitigates phase transitions under different environmental conditions [1]. Collectively, these strategies contribute significantly to enhancing the durability and performance of PSCs, ensuring their viability in commercial applications and alignment with sustainable energy initiatives.

Additionally, tandem integration in perovskite solar cells (PSCs) is pivotal for achieving higher efficiencies, drawing attention to the implementation of multi-junction architectures that incorporate silicon, CIGS, or organic layers. These architectures exploit the broad spectrum of sunlight, enabling increased power conversion efficiency by linking different bandgaps of materials [5]. However, the transition from laboratory success to large-scale production presents challenges including scalability, where fabrication techniques must be refined to maintain efficiency in larger modules [6]. The environmental impact of these tandem setups remains a subject of ongoing exploration, as integrating diverse materials necessitates sustainable practices throughout the lifecycle of the solar cells [3]. Addressing commercialization prospects requires interdisciplinary efforts to balance efficiency, cost, and material sustainability, ultimately positioning PSCs as frontrunners in renewable energy sources that adhere to environmental and economic criteria [5].

3. CONCLUSION

The potential of perovskite solar cells (PSCs) to become a cornerstone of sustainable energy solutions hinges on their remarkable power conversion efficiencies and the promise of environmentally friendly alternatives to traditional solar technologies. Interdisciplinary collaboration is essential to fully realize this potential, as it fosters advancements in material science, engineering, and environmental research, contributing to overcoming current challenges such as stability and scalability. Key insights for future research directions revolve around the development

of lead-free compositions to mitigate toxicity issues, alongside advancements in interface engineering and device architecture to enhance longevity and efficiency. Addressing remaining challenges, such as the environmental impact and commercial scalability of PSCs, will require sustained efforts across various scientific disciplines. Ultimately, these concerted efforts could pave the way for PSCs to play a significant role in the global transition towards renewable and sustainable energy systems.

REFERENCES

1. Y. Chen, X. Liu, T. Wang, and Y. Zhao, "Highly stable inorganic lead halide perovskite toward efficient photovoltaics," *Accounts of Chemical Research* **54**, 3452–3461 (2021).
2. F. Azri, A. Meftah, N. Sengouga, and A. Meftah, "Electron and hole transport layers optimization by numerical simulation of a perovskite solar cell," *Solar Energy* **181**, 372–378 (2019).
3. J. Y. Kim, J. W. Lee, H. S. Jung, H. Shin, and N. G. Park, "High-efficiency perovskite solar cells," *Chemical Reviews* **120**, 7867–7918 (2020).
4. X. Wu, B. Li, Z. Zhu, C. C. Chueh, and A. K. Y. Jen, "Designs from single junctions, heterojunctions to multijunctions for high-performance perovskite solar cells," *Chemical Society Reviews* **50**, 13090–13128 (2021).
5. F. Martinho, "Challenges for the future of tandem photovoltaics on the path to terawatt levels: a technology review," *Energy & Environmental Science* **14**, 3840–3871 (2021).
6. M. D. Bastiani, A. S. Subbiah, E. Aydin, F. H. Isikgor, T. G. Allen, and S. Wolf, "Recombination junctions for efficient monolithic perovskite-based tandem solar cells: physical principles, properties, processing and prospects," *Materials Horizons* **7**, 2791–2809 (2020).